

How to Order Die-Cut CHO-THERM® Insulators

Standard die-cut parts are ordered using the following Part Number System.

For custom parts contact Chomerics.

WW
60 = Standard die-cut part








XX
11 = No PSA
12 = PSA one side

YYYY
Standard Configuration Drawing Number

ZZZZ
CHO-THERM® Material
Example: 1671, T500, etc.

| RECOMMENDED SCREW/TORQUE | CONFIGURATION | DIMENSIONS (INCHES) | | | | | | | | | ORDERING NUMBER PART NUMBER | |
|--------------------------------|-------------------------|---------------------|-------|------|------|-------|------|---|---|-----------------|------------------------------------|-----------------|
| | | A | B | C | D | E | F | G | H | I | | |
| #4-40 5 in-lb #6-32 6 in-lb | T0-3 | 1.563 | 1.050 | .140 | .080 | | | | | | | WW-XX-D065-ZZZZ |
| | | 1.563 | 1.050 | .140 | .140 | | | | | | | WW-XX-4305-ZZZZ |
| | | 1.593 | 1.100 | .156 | .070 | | | | | | | WW-XX-4511-ZZZZ |
| | | 1.650 | 1.065 | .140 | .046 | | | | | | | WW-XX-D370-ZZZZ |
| | | 1.650 | 1.140 | .122 | .062 | | | | | | | WW-XX-D371-ZZZZ |
| | | 1.650 | 1.140 | .140 | .093 | | | | | | | WW-XX-6875-ZZZZ |
| | | 1.650 | 1.140 | .165 | .062 | | | | | | | WW-XX-D372-ZZZZ |
| | | 1.650 | 1.140 | .140 | .046 | | | | | | | WW-XX-D373-ZZZZ |
| | | 1.650 | 1.140 | .165 | — | | | | | | | WW-XX-D374-ZZZZ |
| | | 1.700 | 1.187 | .156 | .062 | | | | | | | WW-XX-4996-ZZZZ |
| | | 1.730 | 1.250 | .156 | .062 | | | | | | | WW-XX-5442-ZZZZ |
| | | 1.780 | 1.250 | .140 | .093 | | | | | | | WW-XX-D375-ZZZZ |
| | | 1.780 | 1.250 | .165 | .094 | | | | | | | WW-XX-D376-ZZZZ |
| | | 1.780 | 1.250 | .140 | .046 | | | | | | | WW-XX-D377-ZZZZ |
| 2.07 | 1.56 | .122 | .062 | | | | | | | WW-XX-D378-ZZZZ | | |
| #4-40 5 in-lb #6-32 6 in-lb | 3 LEAD T0-3 | 1.65 | 1.140 | .140 | .093 | 1.187 | .430 | | | | WW-XX-D379-ZZZZ | |
| #4-40 5 in-lb #6-32 6 in-lb | 4 LEAD T0-3 | 1.560 | 1.050 | .158 | .080 | 1.170 | | | | | WW-XX-D380-ZZZZ WW-XX-D381-ZZZZ | |
| | | 1.563 | 1.050 | .156 | .063 | 1.187 | | | | | | |
| #4-40 5 in-lb #6-32 6 in-lb | 8 LEAD T0-3 | 1.655 | 1.187 | .156 | .060 | | | | | | WW-XX-D382-ZZZZ | |
| #4-40 5 in-lb #6-32 6 in-lb | 10 LEAD T0-3 | 1.650 | 1.140 | .165 | .040 | | | | | | WW-XX-D383-ZZZZ | |

(1 in-lb = 1.152 kg-cm)

| RECOMMENDED SCREW/TORQUE | CONFIGURATION | DIMENSIONS (INCHES) | | | | | | | | | ORDERING NUMBER PART NUMBER |
|--------------------------------|--|---------------------|-------|------|------|------|------|------|---|---|---|
| | | A | B | C | D | E | F | G | H | I | |
| #4-40 3 in-lb #6-32 4 in-lb | TO-66  | 1.250 | .700 | .140 | .062 | | | | | | WW-XX-4353-ZZZZ WW-XX-5527-ZZZZ WW-XX-4997-ZZZZ WW-XX-D384-ZZZZ |
| | | 1.312 | .762 | .140 | .062 | | | | | | |
| | | 1.375 | .825 | .140 | .062 | | | | | | |
| | | 1.440 | 1.000 | .140 | .075 | | | | | | |
| #4-40 3 in-lb #6-32 4 in-lb | 3 LEAD TO-66  | 1.275 | .750 | .156 | .100 | .960 | | | | | WW-XX-D385-ZZZZ |
| #4-40 3 in-lb #6-32 4 in-lb | 4 LEAD TO-66  | 1.312 | .762 | .140 | .062 | .960 | .200 | .100 | | | WW-XX-D386-ZZZZ |
| #4-40 3 in-lb #6-32 4 in-lb | 9 LEAD TO-66  | 1.440 | 1.000 | .140 | .055 | .960 | .480 | .325 | | | WW-XX-D387-ZZZZ |
| #4-40 3 in-lb #6-32 4 in-lb | MULTI LEAD TO-66  | 1.35 | .800 | .140 | .400 | | | | | | WW-XX-D388-ZZZZ |
| #4-40 2 in-lb | TO-220  | .437 | .312 | .140 | .093 | | | | | | WW-XX-D389-ZZZZ WW-XX-D390-ZZZZ WW-XX-D391-ZZZZ WW-XX-D392-ZZZZ WW-XX-5791-ZZZZ WW-XX-8302-ZZZZ WW-XX-D393-ZZZZ WW-XX-8531-ZZZZ WW-XX-6956-ZZZZ WW-XX-D394-ZZZZ WW-XX-D395-ZZZZ WW-XX-D396-ZZZZ WW-XX-D397-ZZZZ WW-XX-D398-ZZZZ WW-XX-D399-ZZZZ WW-XX-D400-ZZZZ WW-XX-D401-ZZZZ |
| | | .437 | .312 | .140 | .122 | | | | | | |
| | | .500 | .385 | .170 | .120 | | | | | | |
| | | .610 | .560 | .245 | .125 | | | | | | |
| | | .687 | .562 | .218 | .125 | | | | | | |
| | | .710 | .500 | .160 | .141 | | | | | | |
| | | .750 | .410 | .225 | .156 | | | | | | |
| | | .750 | .500 | — | — | | | | | | |
| | | .750 | .500 | .187 | .147 | | | | | | |
| | | .750 | .500 | .187 | .125 | | | | | | |
| | | .750 | .600 | .240 | .150 | | | | | | |
| | | .750 | .600 | .240 | .115 | | | | | | |
| | | .855 | .562 | .218 | .125 | | | | | | |
| | | .855 | .630 | .230 | .093 | | | | | | |
| | | .860 | .740 | .200 | .160 | | | | | | |
| | | 1.125 | .625 | .200 | .145 | | | | | | |
| 1.410 | .810 | .355 | .147 | | | | | | | | |
| #4-40 2 in-lb |  | .910 | .500 | .200 | .125 | .580 | .046 | .265 | | | WW-XX-D402-ZZZZ WW-XX-D403-ZZZZ |
| | | .983 | .750 | .432 | .156 | .665 | .101 | .217 | | | |

(1 in-lb = 1.152 kg-cm)

| RECOMMENDED SCREW/TORQUE | CONFIGURATION | DIMENSIONS (INCHES) | | | | | | | | | ORDERING NUMBER PART NUMBER | |
|----------------------------------|---|---------------------------------------|--------------------------------------|-----------------------------------|-----------------------------------|------|---|---|---|---|--|---|
| | | A | B | C | D | E | F | G | H | I | | |
| #4-40 2 in-lb | TYPE II TO-220 | 1.00 | .500 | .200 | .141 | .626 | | | | | | WW-XX-4969-ZZZZ |
| #10-32 2 in-lb #25-28 7 in-lb | DIODE WASHERS DO-4 DO-5 | .360 .510 .510 .512 .625 | .260 .140 .200 .161 .195 | | | | | | | | | WW-XX-D404-ZZZZ WW-XX-D405-ZZZZ WW-XX-D406-ZZZZ WW-XX-D407-ZZZZ WW-XX-4659-ZZZZ WW-XX-D408-ZZZZ WW-XX-D409-ZZZZ WW-XX-D410-ZZZZ WW-XX-D411-ZZZZ WW-XX-D412-ZZZZ WW-XX-D413-ZZZZ WW-XX-D414-ZZZZ WW-XX-4661-ZZZZ WW-XX-D415-ZZZZ WW-XX-D416-ZZZZ WW-XX-D417-ZZZZ WW-XX-D418-ZZZZ |
| | TO-36 | 1.063 | .690 | .200 | | | | | | | WW-XX-4306-ZZZZ | |
| | TO-5 and TO-18 3 holes 4 holes | .250 .360 .390 | .100 .200 .200 | .036 .040 .040 | | | | | | | WW-XX-D419-ZZZZ WW-XX-4374-ZZZZ WW-XX-D420-ZZZZ WW-XX-D421-ZZZZ WW-XX-D422-ZZZZ WW-XX-D423-ZZZZ | |
| #4-40 2 in-lb | RECTIFIER | .100 1.125 1.250 | .100 1.125 1.250 | .187 .140 .200 | | | | | | | WW-XX-D424-ZZZZ WW-XX-D425-ZZZZ WW-XX-D426-ZZZZ | |
| #4-40 2 in-lb | TIP PACKAGE | .865 .865 .984 .984 1.260 | .650 .650 .787 .787 .787 | .650 .650 — .708 .984 | .140 .140 — .142 .142 | | | | | | WW-XX-5792-ZZZZ WW-XX-D427-ZZZZ WW-XX-D428-ZZZZ WW-XX-D429-ZZZZ WW-XX-D430-ZZZZ | |

(1 in-lb = 1.152 kg-cm)